



VFD / Servo / PLC / HMI

www.simphoenix.com

Shenzhen Simphoenix Electric Technology Co., Ltd

Address: Building A, Huichao Industrial Park, 2nd Rd of Gushu, Xixiang,
Baoan District, Shenzhen, Guangdong, China

Tel: 86-755-26607756, 26910801


Fax: 86-755-26912599, 26919882

E-mail: business01@sunfardrive.com / business02@sunfardrive.com

Web: www.simphoenix.com

V1.3-2022.6





Shenzhen Simphoenix Electric Technology Co., Ltd is a privately operated high-tech enterprise in Shenzhen, as approved by the state and also a software enterprise recognized by Shenzhen Science and Information Bureau.

Established in Feb. 2004, Simphoenix is committed to be a reliable industrial automation product and solution provider in China, Simphoenix is specialized in R&D, manufacturing and sales of automation control products, our main products include low voltage ac drives,servo system, PLC, HMI. Through 15 years of development, Simphoenix has developed to be one of the most professional industrial solution provider in china.

www.simphoenix.com



E280 Series General Vector AC Drive	01
E500 Series Mini-type AC Drive	06
V800 Series Large-power Vector AC Drive	09
DL100 Series Universal Low-power AC Drive	13
Operation Panel	16
I/O Extension Card	18
Communication Adaptive Card	22
PG Extension Card	27
DBKU Series Breaking Unit	31



CA100 Series Servo Drive	33
CM105 Series Servo Motor	37




EP1S Series Programmable Logic Controller (PLC)	40
EP1 Series IO Expansion Module	43
EP1 Series Analog Module	46
EM3 Series HMI	49

PLATFORM ADVANTAGES

R&D

- Around 62 engineers.
- Invest estimated 4 million USD cost in 2020.
- Masters and doctors accounts for 15%.
- Simulation analysis of drive algorithm and heat design.
- Strong-electricity finite elements analysis platform.




Testing

- EMC labs equipped with advanced testing equipment.
- IGBT vibration and LOW / HIGH temperatures.
- Strict testing methods.
- Wish leading electric low voltage stations.



Manufacture Center

- Over 10,000 square meter of production area.
- Annual output value can achieve 85 million USD.
- 6 automatic production lines imported from Germany.
- Flexible manufacturing.
- Reliable quality.
- Fast delivery.



E280 Series

E280 Series General Vector AC Drive



E280 is developed on the basis of our E series AC drive which originally launched in 2004. Through field test of more than 1.2 million AC drives and continuous improvement and optimization of four generation products, stability and reliability has become the key character of our E series products.

Typical Applications

- Machine tool
- Textile machinery
- Cable machinery
- Petrochemical processing
- Construction
- Transmission



Features

- Strong torque at low frequency. 200% start torque at 0Hz under VC control, 180% start torque at 0Hz under SVC control.
- Standard 5-digit two-line LED panel display and LCD keypad optional.
- Intuitive real-time monitoring to know nearly hundred kinds of parameters, like usage of electricity, running time, input & output voltage and current, error record etc.
- Built-in several system macro and application macro, and it simplifies parameter setting by macro parameter calling.
- Hundreds of combinations of torque and revolution.
- Programmable 16-segment speed running, independent setting of running time, acceleration & deceleration time and moving direction of each segment.
- Flexible configuration of priorities of frequency or rotate speed setting channels.
- Software virtual I/O function with simple parameter setting, it configures virtual I/O flexibly that reduce external interference and simplify wiring.
- Abundant warning and protection functions.

Functions

Typical Function	Multi-step running	15 frequency / speed running, each running direction, time, acc or dec set independently. 7 process PID set (PID control function cancel or not)
	Built-in PID	Built-in PID controller, able to be used by external eqips.
	Awakening sleep	Built-in PID with simple sleep and awakening function
	MODBUS Communication	Standard MODBUS communication protocol (optional), flexible parameter read-write mapping function
	Dynamic Braking	Acting voltage: 650~760V, braking rate: 50~100%
	General Function	Reset after power stop, recovery with failure, motor parameter dynamic / static self-identification, start enable, running enable, start delay, over-current inhibit, over-voltage / low-voltage inhibit, V/F self-defined curve, analog input wave rectification, power-off test, textile machine disturbance (swing frequency) operation
	Communication Linkage Synchronization	It is easy to achieve synchronous drive for several eqips with free selection based on current, torque, power to reach linkage balance.
	Overload Dynamic Balance	It can achieve multi-eqips overload dynamic balance (not limit to communication linkage) to reach torque motor characteristics.
	Strong Start Torque	For the load with strong inertia, static friction, it can set super strong start torque for certain time.
	Setting Priority	User can select priority sequence for all kinds of frequency / rotate speed setting channels freely which is suitable for kinds of combined applications.
Unique Function	Setting Combination	Hundreds of setting combination of frequency, rotate speed, torque etc.
	Timer	Built-in 3 timers with 5 kinds of clock and 6 kinds of startup trigger modes Several door control signals and working modes, 7 output signals
	Counter	2 inner counter, 3 counting pulse edge selection, 6 start trigger modes, 7 output signals
	Macro Parameter	Application macro:Easy for setting and partial solidifying several usual parameter groups, simple parameter setting for general applications. System macro:Convenient for switching equip's running mode (ex. Switching with high and low frequency running mode), Self-defined partial parameters
	Parameter Debugging	Adjust any non-stock parameters with one button stock or give up and recovery
Protection Function	Parameter Display	Shield non-use parameter modules automatically, or display revised, stock, changed parameters selectively.
	Running Protection	Over-current protection, over-voltage protection, short circuit protection, inverter over-heat protection, inverter overload protection, motor overload protection, output lack of phase protection
	Equip Abnormal	Current check abnormal, EEPROM storage abnormal, control unit abnormal, motor over-heat, temperature collection loop failure
	Motor Connection	Motor non-connection, motor 3 phase parameter unbalance, parameter identification wrong
Extension Card	Extension Card	Test and protect extension card compatible or conflict

E280 Series

Specifications

Input and Output	Input Rated Voltage	3AC 380V ±20%;3AC 220V ±20%;		
	Input Frequency	50/60 Hz ±20%		
	Output Voltage	0 V ~ input rated voltage		
	Output Frequency	Low frequency running mode: 0.00~300.00Hz; High frequency running mode: 0.00~400.00Hz;		
	Digital Input	E280-4T0040 and below units (extension unable, optional): Standard built-in 5 digital input (DI) E280-4T0055 and above units (extension available): Standard built-in 6 digital input (DI) Extension to 9, one is for high-speed digital input (extension set optional)		
	Digital Output	E280-4T0040 and below units: Standard built-in 1 digital output (DO) E280-4T0055 and above units: Standard built-in 2 digital input (DO) Be able to extend 1 high-speed DO output (0~100kHz)		
	Pulse Input	0 ~ 100.0kHz pulse input. Connect NPN type OC output (optional)		
	Pulse Output	0 ~ 100.0kHz pulse NPN type OC output (optional)		
	Analog Input	E280-4T0040 and below units (extension unable, optional): Standard built-in: 0 ~ 10V voltage input (Ai1), 0 ~ 20mA current input (AI2); E280-4T0055 and above units (extension available): Standard built-in: 0 ~ 10V voltage input (Ai1), 0 ~ 20mA current input (AI2); Be able to extend 1 AI (-10V~10V dual polarity voltage input);		
	Analog Output	E280-4T0040 and below units (extension unable, optional): Standard built-in: 1 0 ~ 10V analog output signal (0 ~ 20mA current output mode optional) E280-4T0055 and above units (extension available): Standard built-in: 2 0 ~ 10V analog output signal (0 ~ 20mA current output mode optional)		
	Contact Output	Standard one set AC 250V/1A normal open, normal contact, able to extend 1-6 sets normal open and normal close contact.		


Control Characteristics	Control Mode	Closed-loop Vector Control	Open-loop Vector Control	V/F Control
	Start Torque	0 Speed 200%	0 Speed 180%	0 Speed 100%
	Speed Adjustment Range	1:1000	1:200	1:100
	Stable Speed Accuracy	±0.02%	±0.02%	±0.5%
	Torque Control Accuracy	±1%	±5%	--
	Torque Responding Time	≤5ms	≤25ms	--
	Frequency Resolution	Low frequency running mode: 0.01Hz;High frequency running mode: 0.1Hz		
	Frequency Accuracy	Low frequency running mode: digital set—0.01Hz, analog set—highest frequency x 0.1% High frequency running mode: digital set—0.1Hz, analog set—highest frequency x 0.1%		
	Overload Capability	G type: 110%--long term; 150%--90s; 180%--2s;		
		P type: 105%--long term;		
	Carrier Wave Frequency	Three phase voltage vector combined mode: 2.0~12.0kHz; Two phase voltage vector combined mode: 2.0~15kHz; (high frequency mode can be 15kHz)		
	Acc. And Dec. Time	0.01~600.00 Sec./0.01~600.00Min.		
	Magnetic Flow Braking	By increasing motor magnetic flow (30~120% available), motor can achieve fast decreasing braking.		
	DC Braking / Band Brake	Initial frequency of DC braking / bank brake: 0.0~upper frequency, braking / bank brake injecting current 0.0~100.0%		
	Start Frequency	0.0~50.0Hz		

Model Table

Voltage class	Model	Code	General load mode ([F0.15] =0)			Load mode for fan and water pump ([F0.15] =1)		
			Rated capacity (KVA)	Rated current (A)	Suitable motor (KW)	Rated capacity (KVA)	Rated current (A)	Suitable motor (KW)
Three phase 220V	E280-2T0022	000M580230022	3.8	10	2.2	—	—	—
	E280-2T0030	000M580230030	5.3	14	3	—	—	—
	E280-2T0040	000M580230040	6.5	17	4	—	—	—
	E280-2T0055	000M580230055	9.5	25	5.5	—	—	—
	E280-2T0075	000M580230075	12.6	33	7.5	—	—	—
	E280-2T0090	000M580230090	14.9	37	9	—	—	—
	E280-2T0110	000M580230110	17.5	46	11	—	—	—
	E280-2T0150	000M580230150	22.9	60	15	—	—	—
	E280-2T0185	000M580230185	28.6	75	18.5	—	—	—
	E280-2T0220	000M580230220	32.4	85	22	—	—	—
	E280-2T0300	000M580230300	41.9	110	30	—	—	—
	E280-2T0370	000M580230370	51.5	135	37	—	—	—
	E280-2T0450	000M580230450	64.8	170	45	—	—	—
	E280-2T0550	000M580230550	78.1	205	55	—	—	—
	E280-2T0750	000M580230750	101	265	75	—	—	—
	E280-2T0900	000M580230900	122	320	90	—	—	—
	E280-2T1100	000M580231100	145	380	110	—	—	—
	E280-2T1320	000M580231320	172	450	132	—	—	—
	E280-2T1600	000M580231600	204	535	160	—	—	—
Three phase 380V	E280-4T0011G/4T0015P	000M580430011	2.0	3.0	1.1	2.4	3.7	1.5
	E280-4T0015G/4T0022P	000M580430015	2.4	3.7	1.5	3.6	5.5	2.2
	E280-4T0022G/4T0030P	000M580430022	3.6	5.5	2.2	4.9	7.5	3.0
	E280-4T0030G/4T0040P	000M580430030	4.9	7.5	3.0	6.3	9.5	4.0
	E280-4T0040G/4T0055P	000M580430040	6.3	9.5	4.0	8.6	13.0	5.5
	E280-4T0055G/4T0075P	000M580430055	8.6	13.0	5.5	11.2	17.0	7.5
	E280-4T0075G/4T0090P	000M580430075	11.2	17.0	7.5	13.8	21	9.0
	E280-4T0090G/4T0110P	000M580430090	13.8	21	9.0	16.5	25	11
	E280-4T0110G/4T0150P	000M580430110	16.5	25	11	21.7	32	15
	E280-4T0150G/4T0185P	000M580430150	21.7	32	15	25.7	37	18.5
	E280-4T0185G/4T0220P	000M580430185	25.7	37	18.5	29.6	45	22
	E280-4T0220G/4T0300P	000M580430220	29.6	45	22	39.5	60	30
	E280-4T0300G/4T0370P	000M580430300	39.5	60	30	49.4	75	37
	E280-4T0370G/4T0450P	000M580430370	49.4	75	37	62.5	95	45
	E280-4T0450G/4T0550P	000M580430450	62.5	95	45	75.7	115	55
	E280-4T0550G/4T0750P	000M580430550	75.7	115	55	98.7	150	75
	E280-4T0750G/4T0900P	000M580430750	98.7	150	75	116	176	90
	E280-4T0900G/4T1100P	000M580430900	116	176	90	138	210	110
	E280-4T1100G/4T1320P	000M580431100	138	210	110	171	260	132
	E280-4T1320G/4T1600P	000M580431320	171	260	132	204	310	160
	E280-4T1600G/4T1850P	000M580431600	204	310	160	237	360	185
	E280-4T1850G/4T2000P	000M580431850	237	360	185	253	385	200
	E280-4T2000G/4T2200P	000M580432000	253	385	200	276	420	220
	E280-4T2200G/4T2500P	000M580432200	276	420	220	313	475	250
	E280-4T2500G4T/2800P	000M580432500	313	475	250	352	535	280
	E280-4T2800G/4T3150P	000M580432800	352	535	280	395	600	315
	E280-4T3150G/4T3500P	000M580433150	395	600	315	428	650	350
	E280-4T3500G/4T4000P	000M580433500	428	650	480	480	730	400
	E280-4T4000G/4T4500P	000M580434000	480	720	527	527	800	450

E280 Series

Installation and Dimension Figure



Model number (Three-phase 380 V)	Model number (Three-phase 220 V)	W1 (mm)	W (mm)	H1 (mm)	H (mm)	D (mm)	Screw (Spec.)
E280-4T0011G/0015P	—	87	97	152	162	130	M4
E280-4T0015G/0022P	—						
E280-4T0022G/0030P	—	95	105	190	200	146	M4
E280-4T0030G/0040P	—						
E280-4T0040G/0055P	—						
E280-4T0055G/0075P	E280-2T0022	121	135	234	248	175	M4
	E280-2T0030						
E280-4T0075G/0090P	E280-2T0040	146	160	261	275	179	M5
E280-4T0090G/0110P	—	Up:169 Down:166	180	290	305	179	M5
E280-4T0110G/0150P	E280-2T0055						
E280-4T0150G/0185P	E280-2T0075	160	210	387	405	202	M6
E280-4T0185G/0220P	E280-2T0090						
E280-4T0220G/0300P	E280-2T0110	160	250	422	445	216	M8
E280-4T0300G/0370P	E280-2T0150						
E280-4T0370G/0450P	E280-2T0185	271	300	545	567	250	M8
E280-4T0450G/0550P	E280-2T0220						
E280-4T0550G/0750P	E280-2T0300						
E280-4T0750G/0900P	E280-2T0370	344	381	588	614	298	M8
E280-4T0900G/1100P	E280-2T0450	380	510	710	740	270	M8
E280-4T1100G/1320P	E280-2T0550						
E280-4T1320G/1600P	E280-2T0750						
E280-4T1600G/1850P	E280-2T0900	400	580	760	793	300	M10
E280-4T1850G/2000P	—						
E280-4T2000G/2200P	E280-2T1100	500	700	960	1000	340	M10
E280-4T2200G/2500P	E280-2T1320						
E280-4T2500G/2800P	—	580	730	1103	1130	355	M10
E280-4T2800G/3150P	E280-2T1600						
E280-4T3150G/3500P	—						
E280-4T3500G/4000P	—	600	760	1170	1200	400	M12
E280-4T4000G/4500P	—						

E500 Series Universal Mini-type AC Drive



E500 series AC Drive is developed based on new hardware platform, which is characterized with extraordinary performance, complete protection functions, small structure, elegance and durability. Optional control keyboard can be used flexibly by users according to requirements. It is especially configured with a status indicator to achieve keyboard-free operation and basic operation status monitor.

Typical Applications

- Textile
- Food
- Transmission
- Ceramics
- Grinding machine
- Centrifugal machine
- Engraving machine
- Terminal machine, Wire-cutting machine, Dividing and cutting machine etc.

Features

- SVC,V/F control.
- Highly adaptive to grid voltage, with endurable to $\pm 20\%$ fluctuation.
- Special self-adaptive control technology, allowing automatic current-limiting, voltage-limiting and under-voltage suppression during operation.
- Standard RS485 communication interface, optional MODBUS protocol and Simphoenix self-defined protocol, with linkage of inverter and PLC, or other industry control equipments easily.
- The panel supports hot-plugging applicable for system integration for various applications.
- Vivid real-time monitor, allowing for monitoring input and output current, voltage etc. in real time.
- 4-channel multifunctional input terminals, with 29 kinds of terminal function definitions, 16 kinds of programmable status outputs, hence enabling flexible parameters control.
- Built-in counter is able to conduct simple counting with match of multifunctional terminals.
- Internally integrated and optimized PID controller, facilitating to conduct closed-loop control over temperature, etc. which is able to simplify control system structure to reduce cost.

E500 Series

Functions

Feature	Specific application parameter, simple PLC, multi-segment running, custom V/F curve, various terminal function definition, RS485 communication, communication linkage
Control feature	VVVF vacuum voltage vector loading-capacity: 110%--long-term, 150% --60s, 180% --2s
Protection	overcurrent, overvoltage, undervoltage, over-heat, short circuit, output phase lack

Specifications


Input voltage (U1), frequency	3AC 380V ±20%, 50/60Hz 1AC 220V ±20%, 50/60Hz
Power range	3AC 380V ±20%, 0.7 kW~9.0kW 1AC 220V ±20%, 0.4kW~7.5kW
Output voltage	3AC 0~380V 3AC 0~220V
Output frequency	0.0~400.0Hz
Carrier frequency	1.5~10.0kHz (along with the power)
Control mode	SVC,V/F
Digital input/output	Standard 4 digital input (X) Standard 1 digital output (OC); Standard 1 relay output(TA-TC)
Analog input/output	Voltage input (AI) (optional 0-20ma current input mode) , 1 0-10V analog output signal (AO)
Communication interface	Optional RS485 interface, Support MODBUS communication protocol
Braking unit	Optional configured
Peripheral interface	Provide 2 outward power source channel, one is +10V/10mA or +5V/50mA, the other is +24V/50mA
Install	Optional wall mounted and orbital
Protection class	IP20
Certificate	CE

Model Table


Voltage class	Model	Code	Rated capacity (KVA)	Suitable motor (KW)	Rated current (A)
Single phase 220V	E500-2S0004(B)	000M550220004(B)	1.1	0.4	3.0
	E500-2S0007(B)	000M550220007(B)	1.9	0.75	5.0
	E500-2S0015(B)	000M550220015(B)	2.9	1.5	7.5
	E500-2S0022(B)	000M550220022(B)	3.8	2.2	10.0
	E500-2S0030(B)	000M550220030(B)	5.3	3.0	14.0
	E500-2S0040(B)	000M550220040(B)	6.3	4.0	16.5
	E500-2S0055(B)	000M550220055(B)	9.5	5.5	25
	E500-2S0075(B)	000M550220075(B)	12.6	7.5	33
Three phase 380V	E500-4T0007(B)	000M550430007(B)	1.6	0.75	2.5
	E500-4T0015(B)	000M550430015(B)	3.0	1.5	4.5
	E500-4T0022(B)	000M550430022(B)	3.6	2.2	5.5
	E500-4T0030(B)	000M550430030(B)	5.0	3.0	7.5
	E500-4T0040(B)	000M550430040(B)	6.3	4.0	9.5
	E500-4T0055(B)	000M550430055(B)	8.6	5.5	13
	E500-4T0075(B)	000M550430075(B)	11.2	7.5	17
	E500-4T0090(B)	000M550430090(B)	13.8	9.0	21

Note: The model with a suffix of "B" has braking unit and RS485 interface.

Installation and Dimension Figure



Class I Suitable for:
E500-2S0004(B)~E500-2S0007(B)/
E500-2S0015(B)~E500-2S0040(B)/
E500-4T0007(B)~E500-4T0040(B)




Class II Suitable for:
E500-2S0055(B)/E500-4T0055(B)~4T0075(B)/
E500-2S0075(B)/E500-4T0090(B)

Inverter model (Three phase 380V)	Inverter model (Single phase 220V)	W1(mm)	W(mm)	H1(mm)	H(mm)	D(mm)	Screw
—	E500-2S0004(B)	67.5	81.5	132.5	148	134.5	M4
—	E500-2S0007(B)						
E500-4T0007(B)	—	86.5	101.5	147.5	165	154.5	M4
E500-4T0015(B)	E500-2S0015(B)						
E500-4T0022(B)	E500-2S0022(B)						
E500-4T0030(B)	E500-2S0030(B)	100	110	190	205	169.5	M5
E500-4T0040(B)	E500-2S0040(B)						
E500-4T0055(B)	—	121	135	234	248	186	M4
E500-4T0075(B)							
E500-4T0090(B)	E500-2S0055(B)	146	160	261	275	190	M5
	E500-2S0075(B)						

V800 Series

V800 Series High-performance Vector AC Drive



V800 series AC drive is based on new vector control platform that built-in control algorithms of closed-loop vector, open-loop vector, V/F control, torque control and V/F separation control, which can meet each kind of complicated control application. It can extend three extension cards, with hundreds of warning functions that will pre-alarm to avoid failure shutdown.

Typical Applications

- Hoisting
- Machine tool
- Textile machinery
- Food packing
- Cable machinery
- Petrochemical processing
- Washing equipment, Centrifugal machine



Features

- Intergrated leading permanent magnet synchronous motor control algorithm.
- Low speed high torque output, 200% starting torque at 0 speed.
- Quick torque response, <5ms.
- Steady speed precision up to $\pm 0.02\%$.
- Power above 3.0kw Inverter with LCD screen as standard.
- Completely new design of switch power supply, reduce failure rate.
- Optimized drive protection function.
- Optional DP, CANopen, modbus for integrated automation.
- Independent airduct design, to ensure electrical isolation.
- Fully enclosed design of electrical part, multilayer conformal coating.

Functions

Features	Outage restart, fault reset, start allowed to enable, running allowed to enable, overcurrent suppression, start delay, overvoltage/undervoltage suppression, analog input curve correction, disconnect detection, swing mode, magentic break, DC break, band type break, wakeup and sleep, temperature detection, analog I/O terminal, spindle orientation, synchronous communication, load dynamic balancing, dual parameter chanel, timer, counter, macroparameter, strong starting torque.
Control feature	Close-loop vector control : 200% starting torque at zero speed, speed range 1: 1000.The steady speed precision $\pm 0.02\%$; torque responding time $\leq 5\text{ms}$. Loading-capacity: General-load Loading capacity: 110%--long-term; 150%--60s, 180%--5s. steady-load mode: 105%--long-term; 120%--60s; 150%--1s.
Protection	Power source: three phase supply unbalance protection. Running protection: overcurrentct protection, overvoltage protection, over temperature protection, inverter over-load protection, motor over-load protection, output phase lack protection, modular drive protection. Equipment malfunction: current detect anomalies, EEPROM memory unit error, control unit anomalies, motor over-heat, input signal anomalies, temperature measurement circuit error . Motor connection: motor disconnected, motor three phase unbalance, parameter identification error. Expansion card : expansion card conflict and compatibility test.

Specifications


Input voltage, frequency	3AC 380V $\pm 20\%$; 50/60Hz
Power range	3AC 380V $\pm 20\%$; 1.1kW~800kW
Output voltage	3AC 0~380V
Ourput frequency	Low frequency mode: 0.0~300.00Hz High frequency mode: 0.0~2000.0Hz
Carrier frequency	3 phase vector synthesis: 1.5~12.0kHz
Control mode	Close-loop vector control; open-loop vector control; V/F control
Digital output/input	Standard 6 digital input (DI), extensible Standard 2 digital output (DO), extensible
Pulse input/output	0.0~100.0kHz pulse input 0.0~100.0kHz pulse output (OC signal/standard I/O extension card)
Analog input/output	V800-4T0030G/4T0040P and models below Standard configuration : 1 0~10V voltage input(AI1); 1 0~20mA current input(AI2); 1 0~10V voltage output (optional 0-20mA current output). Optional configuration : 1 0~10V(-10V~10V swappable) voltage input(AI1). V800-4T0040G/4T0055P and models above Standard configuration : 1 0~10V voltage input(AI1); 1 0~20mA current input(AI2); 2 0~10V voltage output (optional 0-20mA current output). Optional I/O : 1 -10V~10V voltage input(AI3)
Protocol	Extensible for MODBUS protocol (standard RS485 interface) and profibus-DP CANopen protocol
Bulit-in	Power above 75kW built-in DC reactor
Braking unit	Power below 22kW are equipped with braking unit
Peripheral interface	DC24V power source, maximum input current: 100mA
Install	Wall mounted (Power above 220kW are available for cabinet)
Protection class	IP20
Certificate	CE

V800 Series

Model Table

Voltage class	Model	Code	General load pattern			Steady load pattern		
			Rated capacity (KVA)	Rated current (A)	Suitable motor (KW)	Rated capacity (KVA)	Rated current (A)	Suitable motor (KW)
Three phase 380V	V800-4T0011G/4T0015P	006M800430011	2.0	3.0	1.1	2.4	3.7	1.5
	V800-4T0015G/4T0022P	006M800430015	2.4	3.7	1.5	3.6	5.5	2.2
	V800-4T0022G/4T0030P	006M800430022	3.6	5.5	2.2	4.9	7.5	3.0
	V800-4T0030G/4T0040P	006M800430030	4.9	7.5	3.0	6.3	9.5	4.0
	V800-4T0040G/4T0055P	006M800430040	6.3	9.5	4.0	8.6	13.0	5.5
	V800-4T0055G/4T0075P	006M800430055	8.6	13.0	5.5	11.2	17.0	7.5
	V800-4T0075G/4T0090P	006M800430075	11.2	17.0	7.5	13.8	21	9.0
	V800-4T0090G/4T0110P	006M800430090	13.8	21	9.0	16.5	25	11
	V800-4T0110G/4T0150P	006M800430110	16.5	25	11	21.7	33	15
	V800-4T0150G/4T0185P	006M800430150	21.7	33	15	25.7	39	18.5
	V800-4T0185G/4T0220P	006M800430185	25.7	39	18.5	29.6	45	22
	V800-4T0220G/4T0300P	006M800430220	29.6	45	22	39.5	60	30
	V800-4T0300G/4T0370P	006M800430300	39.5	60	30	49.4	75	37
	V800-4T0370G/4T0450P	006M800430370	49.4	75	37	62.5	95	45
	V800-4T0450G/4T0550P	006M800430450	62.5	95	45	75.7	115	55
	V800-4T0550G/4T0750P	006M800430550	75.7	115	55	98.7	150	75
	V800-4T0750G/4T0900P	006M800430750	98.7	150	75	116	176	90
	V800-4T0900G/4T1100P	006M800430900	116	176	90	138	210	110
	V800-4T1100G/4T1320P	006M800431100	138	210	110	171	260	132
	V800-4T1320G/4T1600P	006M800431320	171	260	132	204	310	160
	V800-4T1600G/4T1850P	006M800431600	204	310	160	237	360	185
	V800-4T1850G/4T2000P	006M800431850	237	360	185	253	385	200
	V800-4T2000G/4T2200P	006M800432000	253	385	200	276	420	220
	V800-4T2200G/4T2500P	006M800432200	276	420	220	313	475	250
	V800-4T2500G/4T2800P	006M800432500	313	475	250	352	535	280
	V800-4T2800G/4T3150P	006M800432800	352	535	280	395	600	315
	V800-4T3150G/4T3500P	006M800433150	395	600	315	428	650	350
	V800-4T3500G/4T4000P	006M800433500	428	650	350	480	730	400
	V800-4T4000G/4T4500P	006M800434000	480	730	400	527	800	450
	V800-4T4500G/4T5000P	006M800434500	527	800	450	592	900	500
	V800-4T5000G/4T5600P	006M800435000	592	900	500	658	1000	560
	V800-4T5600G/4T6300P	006M800435600	658	1000	560	737	1120	630
	V800-4T6300G/4T7000P	006M800436300	737	1120	630	823	1225	700
	V800-4T7000G/4T8000P	006M800437000	823	1225	700	955	1450	800
	V800-4T8000G/4T9000P	006M800438000	955	1450	800	1053	1600	900

Installation and Dimension Figure



Inverter model (Three phase 380V)	W1 (mm)	W (mm)	H1 (mm)	H (mm)	D (mm)	Screw
V800-4T0011G/4T0015P	87	97	152	162	130	M4
V800-4T0015G/4T0022P						
V800-4T0022G/4T0030P						
V800-4T0030G/4T0040P	95	105	190	200	146	M4
V800-4T0040G/4T0055P						
V800-4T0055G/4T0075P						
V800-4T0075G/4T0090P	121	135	234	248	175	M4
V800-4T0090G/4T0110P						
V800-4T0110G/4T0150P						
V800-4T0150G/4T0185P	Up:169 Down:166	180	261	275	179	M5
V800-4T0185G/4T0220P						
V800-4T0220G/4T0300P						
V800-4T0300G/4T0370P	160	210	387	405	202	M6
V800-4T0370G/4T0450P						
V800-4T0450G/4T0550P						
V800-4T0550G/4T0750P	160	250	422	445	216	M8
V800-4T0750G/4T0900P						
V800-4T0900G/4T1100P						
V800-4T1100G/4T1320P	200	300	558	567	250	M8
V800-4T1320G/4T1600P						
V800-4T1600G/4T1850P						
V800-4T1850G/4T2000P	240	340	702	717	280	M10
V800-4T2000G/4T2200P						
V800-4T2200G/4T2500P						
V800-4T2500G/4T2800P	300	400	700	717	280	M10
V800-4T2800G/4T3150P						
V800-4T3150G/4T3500P						
V800-4T3500G/4T4000P	300	450	860	890	350	M10
V800-4T4000G/4T4500P						
V800-4T4500G/4T5000P						
V800-4T5000G/4T5600P	450	580	925	950	380	M12
V800-4T5600G/4T6300P						
V800-4T6300G/4T7000P						
V800-4T7000G/4T8000P	500	640	1240	1265	400	M12
V800-4T8000G/4T9000P						
V800-4T9000G/4T10000P						
V800-4T10000G/4T11000P	---	900	---	2100	600	---
V800-4T11000G/4T12000P						
V800-4T12000G/4T13000P						
V800-4T13000G/4T14000P	---	1000	---	2100	600	---
V800-4T14000G/4T15000P						
V800-4T15000G/4T16000P						
V800-4T16000G/4T17000P	---	1200	---	2100	600	---
V800-4T17000G/4T18000P						
V800-4T18000G/4T19000P						

DL100 Series

DL100 Series Universal Low-power AC Drive



DL100 series is a small general-purpose inverter developed based on a new software and hardware platform to meet more market needs. It has the characteristics of small size, simple operation, complete protection functions, stable and reliable operation, and can be flexibly applied to various process sites.

Typical Applications

- Food Machinery
- Engraving Machine
- Textile machinery
- Package and Transport
- Machine Tool applications
- Centrifuges



Features

- Based on new hardware platform, high reliability with stringent test
- High frequency can reach 600.00Hz, and the frequency control accuracy controlled within 0.1%
- 4 multi-function input terminals, up to 12 channel combinations, to achieve flexible parameters control
- Multiple protection functions and fault checking mechanisms are convenient for later maintenance
- Support the monitoring of nearly hundreds of parameters such as power, running time, input/output current and voltage, fault record in real time
- Programmable 7-segment speed operation, each segment's running time, acceleration/deceleration time, and running direction are independently adjustable
- Equipped with RS485 communication interface, standard MODBUS protocol can easily realize real-time communication with PLC, industrial computer and other equipment, and has the function of linkage and synchronization control
- Supports adaptive control technology, automatic voltage stabilization and current limiting functions, stable operation even in an environment with unstable grid voltage and current

Functions

Features	Simple PLC function, multi-speed operation, custom V/F curve, definition of various terminal functions, RS485 communication, communication linkage
Control feature	VVVF space voltage vector Loading-capacity: 110%--long term; 150%--60s; 180%--2s
Protection	Operation protection: overcurrent protection, overvoltage protection, undervoltage protection, inverter overheating protection, inverter overload protection, motor overload protection, short circuit protection

Note: In the case of sudden acceleration and deceleration and heavy load, please choose other vector inverters

Specifications


Input voltage(U1), frequency	3AC 380V~415V $\pm 10\%$; 50/60Hz 1AC 220V~240V $\pm 10\%$; 50/60Hz
Power range	3AC 380V 0.7kW~7.5kW 1AC 220V 0.4kW~2.2kW
Output voltage U2	0~U1
Ourput frequency	0.0~600.00Hz
Carrier frequency	2.0~8.0kHz
Control mode	V/F control
Digital output/input	Standard 4 digital input (X), Standard 1 digital output (OC) Standard 1 relay output (TA-TC)
Analog input/output	0~10V voltage input(AI1); (0~20mA current input mode available) 1 0~10V analog output signal (AO), Upper and lower limits can be set separately
communication interface	RS485 communication interface, MODBUS protocol, user-difined protocol
Braking unit	DL100(B) Standard with braking unit
Peripheral interface	Provide 2 channels of power supply, 1 channel is +10V/10mA, the other is + 24V/50mA
Protection class	IP20
Design Criterion	IEC61800-3, IEC61800-5

DL100 Series


Model Table

Voltage class	Model	Rated capacity (KVA)	Suitable motor (KW)	Rated current (A)
Single phase 220V	DL100-2S0004(B)	1.1	0.4	3.0
	DL100-2S0007(B)	1.9	0.75	5.0
	DL100-2S0015(B)	2.9	1.5	7.5
	DL100-2S0022(B)	3.8	2.2	10.0
	DL100-2S0030(B)	5.3	3.0	14.0
	DL100-2S0040(B)	6.3	4.0	16.5
Three phase 380V	DL100-4T0007(B)	1.6	0.75	2.5
	DL100-4T0015(B)	3.0	1.5	4.5
	DL100-4T0022(B)	3.6	2.2	5.5
	DL100-4T0040(B)	6.3	4.0	9.5
	DL100-4T0055(B)	8.6	5.5	13
	DL100-4T0075(B)	11.2	7.5	17

Installation and Dimension Figure



I和II类机型
DL100-2S0004(B)~DL100-2S0015(B)
DL100-4T0007(B)~ DL100-4T0015(B)



III类机型
DL100-2S0022(B)~ DL100-2S0040(B)
DL100-4T0022(B)~ DL100-4T0075(B)

Inverter model (Three phase 380V)	Inverter model (Single phase 220V)	W1(mm)	W(mm)	H1(mm)	H(mm)	D(mm)	Screw
--	DL100-2S0004(B)	59	68	139	148	110	M4
DL100-4T0007(B)	DL100-2S0007(B)						
DL100-4T0015(B)	DL100-2S0015(B)						
DL100-4T0022(B)	DL100-2S0022(B)	78	88	155	165	113	M4
DL100-4T0040(B)	DL100-2S0030(B)						
DL100-4T0055(B)	DL100-2S0040(B)	99	109	199	209	135	M4
DL100-4T0075(B)	--						

Operation panel

Serial	Name	Model	Code	Models	Remarks
1	Single LED standard keypad	DPNL300EES	050M007031301	E500	E0313, Standard1.5 meter line
2	Single LED Medium Keypad	DPNL301EFS	050M007031401	E500	E0314, Standard1.5 meter line
3	Single LED mini Keypad	DPNL302EMS	050M007031801	E500	E0318, Standard1.5 meter line
4	LCD Button Keypad	DPNL360CA	050M007360001	V/E280	E0327, Standard1.5 meter line
5	LCD Wheel Keypad	DPNL360CB	050M007360002	V/E280	E0328, Standard1.5 meter line
6	Double LED Button Keypad	DPNL360EA	050M007360003	V/E280	E0315, Standard1.5 meter line
7	Double LED Wheel Keypad	DPNL360EB	050M007360004	V/E280	E0316, Standard1.5 meter line
8	Double LED Button Mini Keypad	DPNL350EM	050M007033701	V/E280	E0337, Standard1.5 meter line
9	Double LED Potentiometer Keypad	DPNL350EN	050M007033601	V/E280	E0336, Standard1.5 meter line

E500 Series

1. Single LED standard keypad
DPNL300EES




Base External installation Figure 5
No Base External installation Figure 6

2. Single LED Medium Keypad DPNL301EFS
(Only for External connection)



No Base External installation Figure 1

3. Single LED mini Keypad
DPNL302EMS



Base External installation Figure 7

V Series, E280 Series

4. LCD Button Keypad
DPNL360CA



Base External installation Figure 2
No Base External installation Figure 3

5. LCD Wheel Keypad
DPNL360CB



Base External installation Figure 2
No Base External installation Figure 3


6. Double LED Button Keypad
DPNL360EA



Base External installation Figure 2
No Base External installation Figure 3

7. Double LED Wheel Keypad DPNL360EB	8. Double LED Button Mini Keypad DPNL350EM	9. Double LED Potentiometer Keypad DPNL350EN
		
Base External installation Figure 2 No Base External installation Figure 3	No Base External installation Figure 4	No Base External installation Figure 4

Hole dimension




Note: the thickness of open sheet metal is not more than 2.0mm

I/O Extension Card

No.	Name	Model	Technical index	Adaptive Models
1	IO extension card (Standard)	IOV-D104	1 channel 485 communication interface; $\pm 10V$ auxiliary power; 1 channel analog voltage input; 2 channel digital inputs; 1 channel high-speed programmable pulse input; 1 high-speed programmable OC output; 1 programmable relay output.	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
2	IO extension card	IOV-A102	1 group RS485 channel; + 10v auxiliary voltage source; + 24v auxiliary power supply; 4 channel digital inputs; 1 channel high-speed OC output; 2 channel analog inputs; 1 group relay programmable output with normally open and normally closed contacts; 1 channel analog output.	V800-4T0030G/4T0040P and below models, E280-4T0040G/4T0055P and below models.
3	IO extension card	IOV-A103	Provide + 12v auxiliary voltage source; 4 digital input terminals; 1 high-speed digital input terminal; 3 single-ended PG signal input; 2 analog input (voltage and current); 1 group of relay programmable output normally open Normally closed.	V800-4T0030G/4T0040P and below models, E280-4T0040G/4T0055P and below models.
4	IO extension card	IOV-A110	Provide + 15v / 100mA auxiliary voltage source; + 24v / 100mA auxiliary voltage source; 2 digital inputs; 1 asynchronous communication serial port; 1 analog input.	V800-4T0030G/4T0040P and below models, E280-4T0040G/4T0055P and below models.
5	Communication & high-speed pulse expansion card	IOV-A113	3 programmable switch input terminals with rectification function, through external wiring, can choose source input mode or sink input mode; 1 NPN high-speed digital output port with isolation; 1 high-speed digital with isolation Input port; 1 analog input port (voltage or current can be switched); 1 analog output port (voltage or current can be switched); 1 with 485 communication interface; 1 set of programmable relay contact output ports; 1 10V auxiliary power output port; 1 24V auxiliary power output port.	V800-4T0030G/4T0040P and below model, E280-4T0040G/4T0050P and below model.
6	Rectifier input digital terminal expansion card	IOV-D112	3 programmable digital input terminals with rectification function, through external wiring, can choose source input mode or sink input mode; a set of 24VDC / 50mA auxiliary power supply.	V800-4T0030G/4T0040P and below models, E280-4T0040G/4T0055P and below models.



Product Structure and Introduction

1. I/O Extension Card (Standard Type) IOV-D104



Terminal Type	Terminal Name	Function
Communication port	RS+,RS-	RS485 communication port
Auxiliary power	+10V,-10V	Supply ±10V/Max. 10mA power
Analog input	AI3	Analog voltage -10V~10V input, input impedance ≥ 100k Ω
Digital input	DI7,DI8	Valid when OFF with CM port, input frequency ≤ 1kHz
High-speed pulse/digital input	DI9	High-speed programmable pulse input, valid when OFF with CM port, frequency ≤ 100kHz
High-speed pulse/digital output	DO3	High-speed programmable OC output, output frequency ≤ 100kHz
Programmable relay output	TA1	TA1-TB1 normally closed contact; TA1-TC1 normally open contact; Contact capacity: AC 250V/1A
	TB1	
	TC1	
Common port	GND	± 10V, common port of AI3
	CM	Common port of DO3 、 DI7 、 DI8 、 DI9



2. I/O Extension Card IOV-A102



I/O Extension Card Wiring Diagram

Terminal Type	Name	Description	Function
Communication Port	RS+	485 differential signal positive terminal	Standard RS485 communication port
	RS-	485 differential signal passive terminal	
Output power	10V	+10V auxiliary voltage source	Max. loading capacity: 20mA
	24V	+24V auxiliary voltage source	Max. loading capacity: 100mA
Analog input	AI1	Analog input terminal	Input voltage: 0~10V (optional -10V~10V)
	AI2		Input current: 0~20mA
Digital input	DI1	Digital input terminal	Input impedance: R= 4.7KΩ Max. input frequency: 1kHz
	DI2		
	DI3		
	DI4		
Analog output	AO1	Multi-functional analog output terminal	Current output: 0~20mA(load resistance: 0~500Ω);voltage output:0~10V; JP1 connect to V: voltage output; JP1 connect to A: current output
Digital output	DO3	OC output terminal	Max. output frequency: 100kHz; Max. work voltage: 24V; Max. output current: 150mA
Programmable relay output	TA	TA-TB normally closed contact TA-TC normally open contact	Common port of +10V、 AO1、 AI1、 AI2
	TB		
	TC		
Common port	GND	Analog common terminal	Common port of DO3、 DI1、 DI2、 DI3、 DI4
	CM	+24V/digital common terminal	Contact capacity: AC 250V/1A

3. I/O Extension Card IOV-A103





I/O Extension Card Wiring Diagram

IOV-A103 is applicable to V Series/E280 Series

Terminal Type	Name	Function
Auxiliary power	12V	Supply +12V/Max.100mA power
	PGA	Connect NPN type encoder A phase output, max. frequency ≤100 kHz
Single terminal PG signal input	PGB	Connect NPN type encoder B phase output, max. frequency ≤100 kHz
	PGZ	Connect NPN type encoder C phase output, max. frequency ≤100 kHz
Analog input	AI1	Analog voltage: 0 ~ 10V, input impedance ≥ 100kΩ
	AI2	Analog current input: 0 ~ 20mA
Digital input	DI1~DI4	Input frequency ≤ 1kHz
High-speed digital input	DI9	Can work as high-speed pulse input terminal, max. input frequency ≤100kHz
Programmable relay output	TA	TA-TB normally closed contact; TA-TC normally open contact; Contact capacity: AC 220V/ 1A
	TB	
	TC	
Common port	GND	Common port of AI1、 AI2
	CM	Common port of 12V , PGA , PGB , PGZ , DI1~DI4 , DI9

4. I/O Extension Card IOV-A110




I/O Extension Card Wiring Diagram


IOV-A110 is applicable to V Series/E280 Series

Terminal Type	Name	Instructions	Function
Communication port	TX	Asynchronous serial port sender	Communication asynchronous serial port
	RX	Asynchronous serial port receiver	
Output power	24V	+24V voltage source	Maximum load capacity: 100mA
	15V	+15V voltage source	Maximum load capacity: 100mA
Analog input	AI2	Analog input terminal: See applicable models specification parameters F4	Input range: 0~20mA
Digital input	DI1	Digital input terminal: See applicable models specification parameters F3	Input impedance: R = 4.7kΩ Maximum input frequency: 1kHz
	DI2		
Common port	GND	Analog, AI2 common, asynchronous communication Interface public	—
	CM	+15V, +24V Power Supply Common DI1, DI2 common	

5 . Communication and high-speed pulse expansion card IOV-A113




IOV-A113 is applicable to V Series/E280 Series




Termnial Type	Name	Instructions	Function
Commucation	RS+	485 differential signal positive terminal	Standard RS485 communication port,JP1 terminal resistance switch,advised to tun JP1 to ON when used in parallel
	RS-	485 differential signal negative terminal	
Auxiliary power	VS	+10V auxiliary voltage source	Max.loading capacity:20mA
	24V	+24V auxiliary voltage source	Max.loading capacity:100mA
Analog input	AI1	Analog input terminal; See applicable models specification parameters F4	Input range:0~10V;Input current:0~20mA; JP3connect to V:voltage input ;JP3 connect A:current input
Digital input	DI1	Multi-functional input terminal; See applicable models specification parameters F3	Input impedance:R=4.7 KΩ Max.inputfrequency:200Hz Gate valve voltage<16V
	DI2		
	DI3		
Analog output	AO1	Analog output; See applicable models specification parameters F4	Current output:0~20mA; voltage output:0~10V; Output current with impedance specification:0~300Ω; JP1 connect to V:voltage output ;JP1 connect A:current output
Digital input	DI9	High-speed pulse input; See applicable models specification parameters F3	Max.input frequency:100kHz
Digital output	DO3	OC pulse input; See applicable models specification parameters F3	Max.output frequency:100kHz;Max working voltage:24V; Max output current:150mA
Programmable relay output	TA	TA-TB normally closed contact; TA-TC normally open contact; See applicable models specification parameters F3	Contact rating: AC 250V/3A
	TB		
	TC		
Common port	GND	Analog common terminal	Common port of +10V· AO1· AI1
	CM	+24V· pulse input· pulse output common port	Common port of +24V· DO3· DI9
	PLC	DI1、 DI2、 DI3 source/sink input selection terminal	When DI1, DI2 and DI3 are driven by external signals, PLC needs to be connected with external power supply


6 . Rectifier input digital terminal expansion card IOV-D112



IOV-D112 is applicable to V Series/E280 Series



Input signal is NPN sinking input wiring diagram



Input signal is NPN sinking input wiring diagram


Termnial Type	Name	Instructions	Function
Output power	24V	24v auxiliary voltage source positive	Max output current 50mA
	GND	24v auxiliary voltage source ground	
Common port	PLC	DI7、 DI8、 DI9 input terminal source/sink selection terminal, When DI7, DI8 and DI9 are driven by external signals, PLC needs to be connected with external power supply	Voltage output15~24VDC
Digital input terminal	DI7	Multi-functional input terminal DI7	
	DI8	Multi-functional input terminal DI8	
	DI9	Multi-functional input terminal DI9	

Communication Adaptive Card

No.	Name	Model	Technical index	Adaptive Model
1	Modbus communication adaptiveCard	IOV-D105	1 channel 485 communication interface; ± 10V auxiliary power;1analog input	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
2	CANopen communication adaptive card	IOV-D109	Support CAN2.0A communication, comply with ISO11898 standard; comply with CANopen standard protocol DS301v4.02; enhance ESD protection, isolated CAN transceiver interface; low communication delay time, less than 2ms; 4 RPDO, 4 TPDO, each PDO Both can be remapped, PDO transmission type: synchronous periodic trigger, synchronous aperiodic trigger; support for SDO service: support for standard SDO fast transmission mode, access to all inverter parameters through SDO; support for Emergency Protocol: when inverter alarm or warning Actively send Emergency messages	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
3	I/O extension card	IOV-D111	15V auxiliary voltage source; 1 asynchronous communication serial port	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
4	Profibus-DP communication adaptive card	IOV-E108	Supports PROFIBUS-DP protocol,in compliance with EN50170 DPV0 and IEC61158 standards; PROFIBUS-DP is self-adaptive in measuring baud rate with a maximum baud rate of 12Mbps; supports PROFIDRIVE message frame format PPO1 ~ 5; can receive single-ended collector-level open circuit output ,Pull-type output and differential output encoder signals; provide a set of + 12V power supply (load capacity≤ 500mA); provide incremental encoder three-phase differential input standard interface	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
5	Air compressor communication adapter cardcommunication adapter card	IOV-B106	MODBUS protocol conversion, which maps the commonly used access monitoring quantities of air compressors to the corresponding control quantities of Quartet E580, V series inverters (including unit conversion)	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
6	DP communication extension card	IOV-A111 (Main card)	Main card: 1 relay programmable output, 3 digital inputs, 1 digital output, providing + 24V auxiliary power.	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
7	DP communication extension card	IOV-A112 (Vice card)	Vice card: 2 slave address dialers, 1 Profibus plug interface.	

Product Structure and Introduction

1 . Communication Adaptive Card IOV-D105



IOV-D105 is applicable to V Series/E280 Series

Terminal Type	Name	Function
Communication port	RS+, RS-	RS485 communication port
Auxiliary power	+10V, -10V	Supply ±10V/max. 10mA power
Common port	GND	Common port of ±10V and AI3
Analog input	AI3	Analog voltage input (-10V~10V), input impedance ≥100kΩ


2 . CANopen Communication Adaptive Card IOV-D109



IOV-A110 is applicable to V Series/E280 Series

Terminal Type	Name	Function
Communication port	CAN+	CANopen communication physical interface
	CAN-	
Communication cable shielding ground	EARTH	CANopen cable shielding ground
Common port	GND	Protection ground
Knob	Position	Baud Rate
Baud rate selection	0	10kbps
	1	20kbps
	2	50kbps
	3	125kbps
	4	250kbps
	5	500kbps
	6	800kbps
	7	1Mkbps


3. I/O extension card IOV-D111



IOV-D111 is applicable to V Series/E280 Series

Termnial Type	Name	Instructions	Function
Communication port	TX	Asynchronous series port sender	Communication asynchronous series port
	RX	Asynchronous series port receiver	
	15V	15V reference voltage source	Maximum load capacity:100mA
	CM	15V common port,asynchronous communication interface common port	–



4 . Profibus-DP Communication Adaptive Card IOV-E108



IOV-E108 is applicable to V Series/E280 Series

Terminal Type	Name	Function
Profibus differential signal	DP-A-	Receive / send data -N(signal A)
	DP-B+	Receive / send data -P(signal B)
	PGND	Communication cable shielding ground
Standard Profibus bus connector	1	Shielding layer
	3	Receive / send data -P(signal B)
	4	Control -P
	5	5V power earth
	6	5V power
Auxiliary power	+12V	Supply +12V/max. 200mA current
	GD	Power supply referring ground
Differential input	A+	Encoder A phase differential (+12V20%)input, max. frequency ≤100 kHz
	A-	
	B+	Encoder B phase differential (+12V20%)input, max. frequency ≤100 kHz
	B-	
	Z+	Encoder Z phase differential (+12V20%)input, max. frequency ≤100 kHz
	Z-	

5. Air compressor communication adapter cardcommunication adapter card IOV-B106





IOV-B106 used for air compressor controller to access V series / E280 series

Air compressor communication adapter card wiring diagram


Termnial Type	Name	Function
Communication port	485- , 485+	RS485 communication port
	AI1	Voltage input:0~10V
Analog input	AI2	Current input:0~20MA
	GND	Reference point for ± 10,AI3
Common port	CM	Common port for AI1、 AI2

6 . DP communication extension card IOV-A111 (Main card)



DP Communication Card Wiring Diagram

7 . DP communication extension card IOV-A112 (Vice card)



IOV-A111 / A112 DP communication expansion card is an optional communication expansion Card that our company launched with E280 (4.0KW and below) / V350 (3.0KW and below) / V800 (3.0KW and below) series of low-power inverters.

Main card part

Termnial Type	Name	Instructions	Function
Programmable relay output	TA	TA-TB normally closed contact; TA-TC normally open contact; See applicable models specification parameters F3	Contact rating:AC 250V/1A
	TB		
	TC		
Digital input	DI1	Digital input; See applicable models specification parameters F3	Input impedance:R=4.7 KΩ Max.input frequency:200Hz
	DI2		
	DI3		
Digital output	DO3	OC output; See applicable models specification parameters F3	Max.output frequency:100kHz ;Max working voltage:24V; Max output current:150mA
Auxiliary power	+24V	+24V auxiliary voltage source	Max 100mA current
Common port	CM	Power reference ground	Common port of DO3、 DI1、 DI2、 DI3
Sub card connection port	CON1	Main card and Vice card communication interfaces	Communication line length: ≤ 300mm

Vice card part



Termnial Type	Name	Instructions	Function
Slave address dialer	SW1	Single digit of slave address code	The setting range of the hardware slave address is 1 ~ 98; when the slave address dialer sets the slave address to 0, it indicates that the node address of the DP slave is read from the internal EEPROM, and the setting range is 1 ~ 126; When the slave address dialer sets the slave address to 99, it instructs the DP slave configuration parameters to power on to restore the factory default values.
	SW2	Ten-digit of slave address code	
Profibus plug connection	CON1	Stasiun abdi cerdas DP disambungake karo stasiun master PROFIBUS	The bus communication cable is recommended to use Profibus RS-485 type A cable; Characteristic impedance:135Ω~165Ω capacitance: ≤30pf/m Loop resistance: ≤110Ω/km Wire diameter:>0.64mm Conductor cross-sectional area:>0.34mm2
Main card connection port	CON3	Main card and Vice card communication interfaces	Communication line length: ≤ 300mm

PG Extension Card


No.	Name	Model	Adaptive Model	Adaptive Model
1	PG card (Standard)	PGV-C000	1. matching incremental encoder; 2. adaptive TTL gain signal or differential signal; 3. providing +12V / maximum 200mA auxiliary power; 4. 3 differential inputs (A + / A-, B + / B-, Z + / Z-), the max input frequency ≤ 100kHz	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
2	PG signal separation card	PGV-C001	1. matching incremental encoder; 2. providing 3 differential inputs and 3 and5V differential output signals in phase with the input; 3. providing + 5V / max 200mA auxiliary power; 4. 3 differential inputs (A + / A-, B + / B-, Z + / Z-), 3 differential outputs (AO + AO-, BO + / BO-, ZO + / ZO-), the max input frequency ≤ 100kHz	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
3	PG signal separation card	PGV-C005	1. Can receive single-ended collector-level open-circuit output and 5V differential input encoder signals, output open-collector signals; 2. 5V / 500mA (max) voltage source; 3. Incremental encoder three-phase ABZ differential input standard interface , Signal amplitude + 5V ± 20%; 4. three-phase ABZ NPN open collector output interface, withstand voltage 24V; 5. signal frequency : ≤ 100kHz	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
4	PG & communication extension card	PGV-A006	1. 1 programmable relay contact output port; 2. 4 digital input ports; 3. 1 digital output port; 4. 1 isolated PG speed port; 5. 1 485 communication interface; 6. 2 Analog input ports (AI1 voltage or current switchable, AI2 fixed voltage input); 7. 2 analog output ports (AO1 voltage or current switchable, AO2 fixed voltage input); 8. 1 10V auxiliary power output port ; 9. 1 12V auxiliary power output port (for PG speed measurement); 10. 1 24V auxiliary power output port	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.
5	Sine cosine PG card	PGV-C006	1,Matching incremental encoder; 2. Adaptive sine signal or cosine signal; 3. Provide +5V/ Max 100mA auxiliary power; 4. 3 differential input (IA+/IA-,IB+/IB-,IZ+/IZ-), 3 differential output (OA+/OA-,OB+/OB-,OZ+/OZ-) max input frequency ≤ 1MHz	V800-4T0040G/4T0055P and above models, E280-4T0055G/4T0075P and above models.

Product Structure and Introduction

1.PG Card(Standard) PGV-C000





PG Card Differential Input Wiring Diagram




PG Card Single Terminal Input Wiring Diagram

Terminal Type	Name	Function
Auxiliary power	+12V	Supply +12V/max.200mA current
Common port	GD	Common port of power
Differential input	A+	Encoder A phase differential (+12V±20%) input, max. frequency ≤100 kHz
	A-	
	B+	Encoder B phase differential (+12V±20%) input, max. frequency ≤100 kHz
	B-	
	Z+	Encoder Z phase differential (+12V±20%) input, max. frequency ≤100 kHz
	Z-	

2. PG Signal Separation Card PGV-C001





PG Card Differential Input Wiring Diagram




PG Card Single Terminal Input Wiring Diagram

Terminal Type	Name	Function
Auxiliary power	+5V	Supply +5V/ max. 500mA current
Common port	GD	+5V power common port
Differential output	AO+	Encoder A phase differential (+5V±20%) output, max. frequency ≤100 kHz
	AO-	
	BO+	Encoder B phase differential (+5V±20%) output, max. frequency ≤100 kHz
	BO-	
	ZO+	Encoder Z phase differential (+5V±20%) output, max. frequency ≤100 kHz
	ZO-	
Differential input	AI+	Encoder A phase differential (+5V±20%) input, max. frequency ≤100 kHz
	AI-	
	BI+	Encoder B phase differential (+5V±20%) input, max. frequency ≤100 kHz
	BI-	
	ZI+	Encoder Z phase differential (+5V±20%) input, max. frequency ≤100 kHz
	ZI-	

3 . PG Signal Separation Card (OC) PGV-C005





PG Card Differential Input Wiring Diagram



PG Card Single Terminal Input Wiring Diagram



Terminal Type	Name	Function
Auxiliary power	+5V	Supply +5V/ max. 500mA current
Common port	GD	+5V power common port
Open collector output	AO	Encoder A phase open collector output, max. frequency ≤100 kHz, output current <100mA
	BO	Encoder B phase open collector output, max. frequency ≤100 kHz, output current <100mA
	ZO	Encoder Z phase open collector output, max. frequency ≤100 kHz, output current <100mA
Differential input	AI+	Encoder A phase differential (+5V±20%) input, max. frequency ≤100 kHz
	AI-	
	BI+	Encoder B phase differential (+5V±20%) input, max. frequency ≤100 kHz
	BI-	
	ZI+	Encoder Z phase differential (+5V±20%) input, max. frequency ≤100 kHz
	ZI-	

4. PG & Communication Extension Card PGV-A006



Terminal Type	Name	Description	Function
Programmable relay output	TA	TA-TB normally closed contact, TA-TC normally open contact, Please refer to F3 parameter for more details.	Contact capacity: AC 250V/1A
	TB		
	TC		
Digital input	DI1	Digital input: Please refer to F3 parameter for more details.	Input frequency < 1kHz
	DI2		
	DI3		
	DI4		
Digital output	DO1	OC output, please refer to F3 parameter for more details.	Max. work voltage: 24V, max. work current: 150mA
Auxiliary power reference ground	24V	+24V auxiliary voltage source	Max. loading capacity: 200mA
	12V	PG speed test specialized power	Max. loading capacity: 100mA
	CM	Reference ground for 24V、12V、DI、DO、PGA、PGB、PGZ	——
Programmable relay output	PGA	Respectively contact to incremental encoder A、B、Z phase output	Connect NPN type encoder A phase output max. frequency ≤100kHz
	PGB		
	PGZ		
Auxiliary power reference ground	10V	+10V auxiliary voltage source	Max. loading capacity: 16mA
	GND	Reference ground for 10V、AI1、AO1、AI2、AO2	——
Communication port	RS+	485 differential signal positive terminal	——
	RS-	485 differential signal passive terminal	
Analog input	AI1	Analog input terminal Please refer to F4 parameter for more details in Manual.	1. Dial switch to V as voltage input mode, and input voltage range: 0~10V, input impedance: 100K 2. Dial switch to A as current input mode, input current range: 0~20mA
	AI2		Voltage input mode only
Analog output	AO1	Analog output terminal Please refer to F4 parameter for more details in Manual.	1. Dial switch to V as voltage input mode, and output voltage range: 0~10V. Loading resistance >1K 2. Dial switch to V as voltage input mode, and output current range: 0~20mA. Loading resistance <500R
	AO2		Voltage input mode only

5. Sine cosine PG card PGV-C006



Sine cosine PG card PGV-C006 can be used in general industrial sites where the output of motor position sensor is sine cosine signal. Combined with E280, V350 and V800 series converters, it can realize the precise stop and indexing positioning function functions of high-speed spindle motor; It can be widely used in high-end processing equipment with functions such as precise stop tool change and indexing positioning, such as CNC lathe, CNC milling machine, machining center, engraving machine, etc.

Termnial Type	Name	Instructions	Function
Power supply	VCC	Auxiliary power	Supply +5V/max.500mA current
	GND	Common port of power	+5V power reference ground
Differential input	IA+	Sine signal differential input	Peak to peak value<700Mv; 1.75V<DC bias<3.15V; Max frequency<90kHz;
	IA-		
	IB+	Cosine signal differential input	
	IB-		
	IZ+	Zero sine signal differential input	
	IZ-		
RS422 differential output	OA+	Encoder A-phase differential output	Max frequency≤1MHz; Input current≤25mA;
	OA-		
	OB+	Encoder B-phase differential output	
	OB-		
	OZ+	Encoder Z-phase differential output	
	OZ-		

DBKU Series Breaking Unit




The new generation of DBKU has configured with keypad which can easily read the parameters and make all the settings by user ;with new design of hardware and software, it has more functions like current sampling,voltage tracking breaking and overcurrent,overload,short circuit,IGBT straight protections,also it has master and slave function which makes multiple DBKUs are able to work. With all these update fetures,our new breaking unit can work more smoothly and more stable.

Specifications	
Voltage	380V
Breaking Mode	Voltage tracking mode and Voltage hysteresis mode
Response Time	2ms
Action Voltage	620-730V
Overheat Protection	DC bus voltage 850V
Overcurrent Protection	Rated current 2.5 times(incase the breaking resistor is small)
Overload Protection	The lasting time of passing peak current is less than 25S
Protections	Over current,short circuit,overload,overheat,IGBT straight protection
Status Indication	Power source indication,breaking status indication,fault indication
Action Voltage Setting	620-730V set via keypad

Model Table

Voltage class	Model	Code	Power (KW)	Current(A)		Minimun breaking resistor(R)	Breaking resistor power (breaking frequentness=50%)
				Rated(Long-term)	Peak value(Last 25S)		
Three phase 380V	DBKU-30-A	050M005380030	L: 22-45	30	50	23	15kW
			H: 18.5-30				
	DBKU-50-A	050M005380050	L: 55-90	50	100	13	27kW
			H: 37-55				

Dimensions



Model number	W1 (mm)	W (mm)	H1 (mm)	H (mm)	D (mm)	Screw
DBKU-30-A	60	115	194	207	120	M4
DBKU-50-A						

CA100 Series


CA100 Series Servo Drive



CA100 series servo drive is designed based on a new software and hardware platform. With high cost performance CA100 series servo drive is suitable to the application fields like machine tool, engraving machine, textile and packaging. It has position, speed, torque and multiple control mode and is able to enhance functions to meet the requirement of different kinds of applications.

Typical Applications

- Machine tool
- Engraving machine
- Textile equipment
- Packaging machinery
- Cutting machine
- Food processing



Features

- Various control mode like position, speed, torque and multiple compound control.
- Response frequency is 1.5kHz.
- Available of 2500 P/R, 17bit, 20bit multiple encoder.
- With the load inertia integration, load inertia identification and vibration depression dialing device.
- Overload capacity up to 3 times.

Specifications


Basic Specifications	Drive model	CA100T	1R8、3R0、4R5、6R0、7R5、10R	1PH/3PH AC220V -15%~+10% 50/60Hz
		CA100F	4R0、6R0、8R5、12R、20R、25R	3PH AC380V -15%~+10% 50/60Hz
	Control mode	Torque, speed, position, speed/position, torque/position, torque/speed		
	Feedback	Incremental encoder 2500P/R		
	Work condition	Temperature	Working ambient temperature: 0℃~+45℃ (When the environmental temperature is more than +45℃, please make inverter derated.)	
			Storage temperature: -20℃~+60℃	
		Humidity	Below 90%RH, no condensed water	
		Vibration	0.5G(4.9m/s ²)	
		Protecting grade	IP20	
		Altitude	Under 1000m (When >1000m, please derate.)	
Others	1. No electrostatic interference, no strong electric field, no strong magnetic field, no radiation etc.			
	2. No corrosive gas, combustible gas and water, oil, medicine spray.			
	3. Under environment of little dust, dirt, salt and metal powder etc.			
Installation	Pedestal mounted			
Speed control	Control input	1. 8-channel internal command, internal speed is changeable by control input. 2. External analog command. 3. Zero speed clamp		
	Control output	Speed arrival judgment: 3 methods		
	Analog input	1.According to analog voltage to take speed command input, the max. Voltage is ±12V; 2.DC 300rpm/V [factory value], function code Pn029 can modify input proportion setting.		
	Torque limit command	Able to take forward/reverse torque limit separately		
	Speed ratio	1:6000		
	Speed variation rate	Fluctuation of load	0~100% load: under ±0.02% (≤rated speed)	
		Fluctuation of voltage	Rated voltage ± 10%: 0% (≤rated speed)	
		Fluctuation of temperature	25 ±25°C: ± 0.1% (≤rated speed)	
	Torque control precision	±5% (reproduce type)		
	Soft-start time	0~30s (able to set the acceleration time and deceleration time respectively)		
Frequency response characteristic	1.5kHz(Max)			
Position mode	Command pulse	Input pulse kind	1. Symbol + pulse 2. A, B quadrature pulse 3. CCW+CW pulse	
		Input pulse form	Cable-driven (+5V level), open collector (+5V, +12V, +24V level)	
		Input pulse frequency	Max. 500Kpps (difference) / 200Kpps (collector)	
	Electronic gear ratio	3 groups of electronic gear setting, 1 ~ 32767		
	Control input	Deviation counter clear signal, command pulse prohibit input, internal position 8 segments		
Control output	Positioning complete signal, positioning approach judgment			
Torque control	Control input	1. 4-channel of internal torque, able to take control input judgment 2. analog command input		
	Control output	Torque arrival judgment		
	Analog input	1.According to analog voltage to take torque command input, max. Input voltage is ±12V 2.DC 30%/V [factory value], input proportion setting is changeable		
	Speed limit	3 limit methods		
	Input signal	8DI (digital input terminal)	2AI (analog input terminal)	
	Output signal	5DO (digital output terminal)	2AO (analog output terminal, can be used for debugging monitor)	
	Pulse output	A,B,Z differential signal output, Z pulse collector output		
	Protection	Over current, over voltage, under voltage, over load, main circuit detection error, heatsink overheat, over speed, encoder disconnected, CPU error, parameter error		
	Communication	RS485 1:N (N<128), extendable to other communication methods		
Instruction	Built-in keypad, power charge			

CA100 Series

Model Table

Voltage class	Model	Code	Rated current (A)	Maximum Suitable motor (kW)
Single phase 220V	CA100-T1R8AP	022M100200018	1.8	0.20
	CA100-T3R0AP	022M100200030	3.0	0.75
Single/Three phase 220V	CA100-T4R5AP	022M100200045	4.5	1.20
Three phase 220V	CA100-T6R0AP	022M100200060	6.0	1.80
	CA100-T7R5AP	022M100200075	7.5	2.00
	CA100-T10RAP	022M100200100	10.0	2.60
Three phase 380V	CA100-F4R0AP	022M100400040	4.0	1.50
	CA100-F6R0AP	022M100400060	6.0	2.60
	CA100-F8R5AP	022M100400085	8.5	3.80
	CA100-F12RAP	022M100400120	12.0	5.50
	CA100-F20RAP	022M100400200	20.0	7.50
	CA100-F25RAP	022M100400250	25.0	9.80

Drive dimensions



Model	W1 (mm)	W (mm)	H1 (mm)	H (mm)	D (mm)	Screw
CA100-T1R8□□	40	50	150	160	175	M4
CA100-T3R0□□						
CA100-T4R5□□	60	70	150	160	175	M4
CA100-T6R0□□						
CA100-T7R5□□						
CA100-T10R□□	89	100	169	180	200	M5
CA100-F4R0□□						
CA100-F6R0□□						
CA100-F8R5□□						
CA100-F12R□□	80	110	268	280	210	M5
CA100-F20R□□						
CA100-F25R□□						


CM105 Series Servo Motor and Matched CA100 Servo Drive Selection Table

220V						
Capacity(W)	Speed(rpm)	Rated Torque(Nm)	Flange	Motor	Drive	Motor Code
200	3000	0.60	60	CM105-60T06030A1□□□□	T1R8 A	2001
400	3000	1.30	60	CM105-60T13030A1□□□□	T3R0 A	2025
			80	CM105-80T13030A1□□□□	T3R0 A	2028
600	3000	1.90	60	CM105-60T19030A1□□□□	T4R5 A	2055
	3000	2.00	110	CM105-110T20030A1□□□□	T3R0 A	2024
730	2000	3.50	80	CM105-80T35020A1□□□□	T3R0 A	2026
750	3000	2.40	80	CM105-80T24030A1□□□□	T3R0 A	2027
800	2000	4.00	110	CM105-110T40020A1□□□□	T4R5 A	2048
1000	2500	4.00	80	CM105-80T40025A1□□□□	T4R5 A	2050
	2500	4.00	130	CM105-130T40025A1□□□□	T4R5 A	2049
	1000	10.00	130	CM105-130T10110A1□□□□	T4R5 A	2051
1100	3000	3.50	80	CM105-80T35030A1□□□□	T4R5 A	2052
1200	3000	4.00	110	CM105-110T40030A1□□□□	T6R0 A	2074
	2000	6.00	110	CM105-110T60020A1□□□□	T4R5 A	2054
1300	2500	5.00	130	CM105-130T50025A1□□□□	T6R0 A	2075
1500	3000	5.00	110	CM105-110T50030A1□□□□	T6R0 A	2076
	2500	6.00	130	CM105-130T60025A1□□□□	T6R0 A	2077
	1500	10.00	130	CM105-130T10115A1□□□□	T6R0 A	2078
1800	3000	6.00	110	CM105-110T60030A1□□□□	T6R0A	2079
2000	2500	7.70	130	CM105-130T77025A1□□□□	T7R5 A	2082
2300	1500	15.00	130	CM105-130T15115A1□□□□	T10R A	2106
2600	2500	10.00	130	CM105-130T10125A1□□□□	T10R A	2107

380V						
Capacity(W)	Speed(rpm)	Rated Torque(Nm)	Flange	Motor	Drive	Motor Code
1000	1000	10.00	130	CM105-130F10110A1□□□□	F4R0 A	4012
1500	1500	10.00	130	CM105-130F10115A1□□□□	F4R0 A	4013
2300	1500	15.00	130	CM105-130F15115A1□□□□	F6R0 A	4030
2600	2500	10.00	130	CM105-130F10125A1□□□□	F6R0 A	4031
3000	1500	19.00	180	CM105-180F19115A1□□□□	F8R5 A	4049
3700	1000	35.00	180	CM105-180F35110A1□□□□	F12R A	4069
3800	2500	15.00	130	CM105-130F15125A1□□□□	F12R A	4067
4300	1500	27.00	180	CM105-180F27115A1□□□□	F12R A	4070
4500	2000	21.50	180	CM105-180F22120A1□□□□	F12R A	4068
5500	1500	35.00	180	CM105-180F35115A1□□□□	F12R A	4071
5600	2000	27.00	180	CM105-180F27120A1□□□□	F20R A	4084
7300	2000	35.00	180	CM105-180F35120A1□□□□	F20R A	4085
7500	1500	48.00	180	CM105-180F48115A1□□□□	F20R A	4083
10000	2000	48.00	180	CM105-180F48120A1□□□□	F25R A	4101

CM105 Sereis

CM105 Series Servo Motor



CM105 series servo motor is a kind of high-performance permanent magnet synchronous motor, high efficiency and low temperature rise bring energy saving benefits to users; it has strong overload capacity, large starting torque, good static rigidity, strong anti load disturbance capacity; large, medium and small inertia can be selected, which can better adapt to the needs of mechanical stability and high-speed responsiveness. Standard imported incremental encoder, higher reliability, longer life.

Typical Applications

- Packaging machine
- Food processing
- Numerical control machine
- Textile machinery
- Woodworking machinery
- Electronic manufacturing



Features

- Precise position control .
- Strong overload capacity .
- Large starting torque .
- Higher reliability and longer life .

Specifications

Flange range	60、80、110、130、180
Torque range	0.64 N.m~48 N.m
Power range	0.2kW~7.5kW
Insulation resistance	500VDC 100MΩ
Insulation strength	1500VAC 1min
Use environment	-20℃~50℃
Insulation grade	F
Encoder type	Photoelectric increment 2500 lines
Overload capacity	Motor under 180 flange 3 times overload, 180 motor 2.5 times overload


Motor specifications

Motor type	Capacity (W)	Rated current (A)	Rated torque (Nm)	Speed (rpm)	Voltage (V)	Flange	Motor Length L(mm)	
							No Brake	Band-type brake
CM105-60T06030A1 □□□□	200	1.3	0.64	3000	220	60	111	161
CM105-60T13030A1 □□□□	400	2.6	1.27	3000	220	60	135	185
CM105-80T13030A1 □□□□	400	2.0	1.27	3000	220	80	124	167
CM105-80T24030A1 □□□□	750	3.0	2.39	3000	220	80	151	194
CM105-80T35020A1 □□□□	730	3.0	3.50	2000	220	80	179	222
CM105-80T35030A1 □□□□	1100	4.5	3.50	3000	220	80	179	222
CM105-80T40025A1 □□□□	1000	4.4	4.00	2500	220	80	191	234
CM105-110T20030A1 □□□□	600	2.5	2.00	3000	220	110	159	233
CM105-110T40020A1 □□□□	800	3.5	4.00	2000	220	110	189	263
CM105-110T40030A1 □□□□	1200	5.0	4.00	3000	220	110	189	263
CM105-110T50030A1 □□□□	1500	6.0	5.00	3000	220	110	204	278
CM105-110T60020A1 □□□□	1200	4.5	6.00	2000	220	110	219	293
CM105-110T60030A1 □□□□	1800	6.0	6.00	3000	220	110	219	293
CM105-130T40025A1 □□□□	1000	4.0	4.00	2500	220	130	166	223
CM105-130T50025A1 □□□□	1300	5.0	5.00	2500	220	130	171	228
CM105-130T60025A1 □□□□	1500	6.0	6.00	2500	220	130	179	236
CM105-130T77025A1 □□□□	2000	7.5	7.70	2500	220	130	192	249
CM105-130T10110A1 □□□□	1000	4.5	10.00	1000	220	130	213	294
CM105-130T10115A1 □□□□	1500	6.0	10.00	1500	220	130	213	294
CM105-130T10125A1 □□□□	2600	10.0	10.00	2500	220	130	209	290
CM105-130T15115A1 □□□□	2300	9.5	15.00	1500	220	130	241	231
CM105-130F10110A1 □□□□	1000	2.5	10.00	1000	380	130	213	294
CM105-130F10115A1 □□□□	1500	3.5	10.00	1500	380	130	213	294
CM105-130F10125A1 □□□□	2600	6.0	10.00	2500	380	130	209	290
CM105-130F15115A1 □□□□	2300	5.0	15.00	1500	380	130	241	322
CM105-130F15125A1 □□□□	3800	8.8	15.00	2500	380	130	231	312
CM105-180F19115A1 □□□□	3000	7.5	19.00	1500	380	180	232	304
CM105-180F22120A1 □□□□	4500	9.5	21.50	2000	380	180	243	315
CM105-180F27115A1 □□□□	4300	10.0	27.00	1500	380	180	362	334
CM105-180F27120A1 □□□□	5600	13.0	27.00	2000	380	180	262	334
CM105-180F35110A1 □□□□	3700	10.0	35.00	1000	380	180	292	364
CM105-180F35115A1 □□□□	5500	12.0	35.00	1500	380	180	292	364
CM105-180F35120A1 □□□□	7300	16.0	35.00	2000	380	180	292	364
CM105-180F48115A1 □□□□	7500	20.0	48.00	1500	380	180	346	418
CM105-180F48120A1 □□□□	10000	24.0	48.00	2000	380	180	346	418


CM105 Series

Drive dimensions(mm)


60 Flange Motor Dimension




80 Flange Motor Dimension




110 Flange Motor Dimension



130 Flange Motor Dimension



180 Flange Motor Dimension



EP1S Series

EP1S Series Programmable Logic Controller (PLC)

EP1S series PLC is minitype high performance universal PLC with tiny configuration but powerful functions, those are data processing, analog processing, internet communication, high speed counting, high speed pulse output positioning control, floating-point operation and writing EEPROM order superior functions etc.



Typical Applications

- Punch Press
- Textile Machinery
- Wire Drawing
- Package Machines
- Construction
- Brick Stone Machinery
- Electronics
- Pharmacy Equipments etc.



Features

- Main module points: 16point/30point/40point/60point.
- Program capacity: 24K step.
- Basic order counting speed: 0.2~0.5μs.
- High speed pulse output: 4 independent 100 kHz.
- Communication port: 1 RS232 port (program port), 1 RS232/RS485 port.
- Holding when power-off: bit register 3248, word register 2940.
- High speed counting: single phase 8 group: 4x100kHz, 4x10kHz, AB phase 2 group: 1x50kHz, 1x5kHz.

EP1S Series

Specifications

Input Specifications:

EP1S Series			
Items	High-speed terminal X0~X7		Normal terminals
Signal input method		Source/leakage type, user can choose via terminal "S/S"	
Electrical Specifications	Detection voltage	24VDC	
	Input impedance	3.3kΩ	4.3kΩ
	On input	400Ω external circuit resistance is less than	400Ω external circuit resistance is less than
	Off output	24kΩ external circuit resistance is more than	24kΩ external circuit resistance is more than
Filter function	Digital filtering	Has digital filtering function, filtering time can be set among 0ms, 8ms, 16ms, 32ms, 64ms	
	Hardware filtering	All the terminal are hardware filtering except terminal X0~X7 and the filtering time is about 10ms	
High-speed function		The maximum frequency of terminal X0, X1, X2, X3 can reach 100kHz The maximum frequency of terminal X4, X5, X6, X7 can reach 10kHz The sum of input frequency need to be less han 60kHz	
Common terminal		There is only one common terminal which is terminal "S/S"	


Output Specifications

EP1S Series			
Items	Relay output type		Output transistor type
Circuit source voltage	250VAC, 30VDC below		5~24VDC
Circuit isolation	Mechanical isolation of relay		Optocoupler isolation
Action indicattion	When the output of the relay contact close, Indicator lamp on		When the optocoupler is activated , Indicator lamp on
Open leakage current	/		0.1mA/30VDC less than
Minimum load	2mA/5VDC		5mA (5~24VDC)
Maximum Output current	Resistor load	2A/1 point	Y0, Y1, Y2, Y3: 0.3A/1 point
		8A/4 point group common terminal	others: When add 1 point the total allowance will add 0.1A while it is above 8 points
		8A/8 point group common terminal	
	Inductive load	220VAC, 80VA	Y0, Y1, Y2, Y3: 7.2W/24VDC, others:12W/24VDC
		220VAC, 100W	Y0, Y1, Y2, Y3: 0.9W/24VDC, others:1.5W/24VDC
Response time	ON→OFF	20ms Max	Y0, Y1, Y2, Y3: 10μs
	ON→OFF	20ms Max	others: 0.5ms
Maximum output frequency		/	Each channel 4x100 kHz
Output common terminal		Y0—COM0; Y1—COM1; Y2—COM2; Y3—COM3; When after Y2, every 8 terminal can use 1 common terminal at most. Each common terminal is isolated	
fuse protection		No	

Model table

Model	Power Supply Voltage (V)	Input/ Output Point	Digital Input Signal Voltage	Digital Output Type	Digital Input Terminal/ Public Terminal	Digital Output Terminal/ Public Terminal	Analog Input Terminal	Analog Output Terminal	Interruption/ Pulse Input	Pulse Output
EP1S-M1006RA	85~264	10/6	DC 24V	Relay	10/1	6/6	No	No	Yes	No
EP1S-M1006TA	85~264	10/6	DC 24V	Transistor	10/1	6/6	No	No	Yes	Yes
EP1S-M1614RA	85~264	16/14	DC 24V	Relay	16/1	14/6	No	No	Yes	No
EP1S-M1614TA	85~264	16/14	DC 24V	Transistor	16/1	14/6	No	No	Yes	Yes
EP1S-M2416RA	85~264	24/16	DC 24V	Relay	24/1	16/7	No	No	Yes	No
EP1S-M2416TA	85~264	24/16	DC 24V	Transistor	24/1	16/7	No	No	Yes	Yes
EP1S-M3624RA	85~264	36/24	DC 24V	Relay	36/1	24/8	No	No	Yes	No
EP1S-M3624TA	85~264	36/24	DC 24V	Transistor	36/1	24/8	No	No	Yes	Yes

Installation and Dimension Figure



Model	W1(mm)	W(mm)	H1(mm)	H(mm)	D(mm)	Screw
EP1S-M1006RA	120.5	130	81	90	85	M4 screw & 35mm width DIN rail
EP1S-M1006TA						
EP1S-M1614RA	140.5	150				
EP1S-M1614TA						
EP1S-M2416RA	224.5	234				
EP1S-M2416TA						
EP1S-M3624RA						
EP1S-M3624TA						

EP1S Series

EP1 Series I/O Expansion Module



This module is used to expand the digital point of the PLC main module, it adopt auto programing method, easy to use.

Typical Applications

- Punching machine
- Textile
- Wire drawing machine
- Packaging
- Construction machinery
- Brick machine
- Electronic equipment
- Pharmaceutical equipment



Model table

Model	Input point	Output point	Output type
EP1-E0800NN	8	—	—
EP1-E1600NN	16	—	—
EP1-E0008RN	—	8	Relay
EP1-E0008TN	—	8	Transistor
EP1-E0016RN	—	16	Relay
EP1-E0016TN	—	16	Transistor
EP1-E0808RN	8	8	Relay
EP1-E0808TN	8	8	Transistor

Specifications

Input Specifications :

Items		Dimension
signal input method		Source/leakage type, choose via s/s terminal
Electrical Specifications	Detection voltage	24VDC
	Maximum allowance voltage	30VDC
	Maximum surge voltage	35VDC, 0.5s
	Input Resistance	4.3kΩ
	ON voltage/curren	18VDC min/3mA min each channel
	OFF voltage/curren	4VDC max/1mA max each channel
	Maximum allowable leakage current	1mA
	Filtering	Filtering time is about 8ms
Isolation voltage		500VAC 1min

Output Specifications


Items		Output port of repaly	Output port of transistor
External power supply		250VAC, 30VDC below	5~24VDC
Circuit isolation		relay mechanical isolation	optocoupler isolation
Isolation voltage		1500VAC	500VAC
Contact endurance		100000 rated load	/
Contact resistance		≤100mΩ	/
Action instruction		indicator light is on when relay output contact closed	indicator light is on when optocoupler is driven
Open leakage current		/	Less than 0.1 mA / 30 VDC
Minimum load		100mA/5VDC	5mA (5~24VDC)
Maximum Output current	Resistor load	2A/1 point	0.3A/1 point
		8A/4 points group common port	0.8A/4 points
		8A/8 points group common port	1.2A/6 points
	Inductive load	220VAC, 80VA	12W/24VDC
	lamp load	220VAC, 100W	1.5W/24VDC
Response time	ON→OFF	20ms maximum	0.5ms maximum
	ON→OFF	20ms maximum	
Common output port		1 public terminal can connect with 8 terminals at most, and public terminals should be isolated from each other.	

EP1 Series


Terminal instructions

EP1-E0800NN

Inputs terminals:



Air terminal:



EP1-E0016RN/EP1-E0016TN

output terminals:




output terminals:




EP1-E1600NN

Inputs terminals:




Inputs terminals:



EP1-E0808RN/EP1-E0808TN

Inputs terminals:



output terminals:




EP1-E0008RN/EP1-E0008TN

output terminals:




Air terminal:



Terminal definition

Pin marking	Instruction
○	No connection
S/S	To choose input method;connect with external 24VDC positive means chooseleakage method while connect with negtive means another one
Xn	Switch signal input terminal, work with terminal S/S can creat input signal
COMn	Output common port
Yn	Switch signal output terminal

Dimensions(mm)



EP1 Series Analog Module



EP1 series analo module is an external part of our EP1 series main PLC module which can detects voltage signal, current signal also output voltage signal and current signal. High-precision, good stability and strong anti-interference performance can fulfill lots of environment and industrial applications.

Typical Applications

- Textile
- Construction
- Injection molding
- Machinery
- Agricultural automation
- Mining



- Analog input/high-precision output.
- Multi- input/output range can meet different ranging requirement.
- Good stability, good consistency and no need for calibration.
- Can correct the zero-drift and linear error of equipment like transmitter and solenoid valve by Built-in zero and
- Full-scale setting value.

EP1 Series

Specifications

Table 1 output specifications

Items	Dimension					
	Voltage input			Current input		
A/D conversion time	1ms			1ms		
Range	Range	Digital Output	Resolution	Range	Digital Output	Resolutio
	0~10V	0~10000	4.88mV	0~20mA	0~10000	9.77uA
	0~5V	0~10000	2.44mV			
	0~2.5V	0~10000	1.22mV			
	0~1V	0~10000	488uV			
	-10~10V	-10000~10000	9.77mV	-20~20mA	-10000~10000	19.53uA
	-5~5V	-10000~10000	4.88mV			
	-2.5~2.5V	-10000~10000	2.44mV			
	-1~1V	-10000~10000	977uV			
	-0.5~0.5V	-10000~10000	488uV			
Precision	environment 25±5℃: 0.2%			environment 25±5℃: 0.2%		
	environment -40~55℃: 0.5%			environment -40~55℃: 0.5%		
Maximum absolute-input	±24VDC			±50mA		
Isolation method	Analog input and PLC: digital isolator Analog input and external 24V: DC/DC converter; Each analog channel: no isolation					

Table 2 output specifications


Items	Dimension					
	Voltage input			Current input		
A/D conversion time	1ms			1ms		
Range	Range	Digital Output	Resolution	Range	Digital Output	Resolution
	0~10V	0~10000	4.88mV	0~20mA	0~10000	9.77uA
	0~5V	0~10000	2.44mV	4~20mA	0~10000	9.77uA
	-10~10V	-10000~10000	9.77mV	0~24mA	0~10000	11.72uA
	-5~5V	-10000~10000	4.88mV	-	-	-
Precision	environment 25±5℃：0.2% environment -40~55℃：0.5%			environment 25±5℃：0.2% environment -40~55℃：0.5%		
Maximum drive Capability	2kΩ minimum			0~20mA：600Ω maximum 4~20mA：600Ω maximum 0~24mA：500Ω maximum		
Common output port	1 public terminal can connect with 8 terminals at most, and public terminals should be isolated from each other.					

Model table


Module type	Analog input channel number	Analog output channel number	Analog signal type
EP1-E4AD	4	0	Voltage, current
EP1-E4DA	0	4	Voltage, current
EP1-E2AD2DA	2	2	Voltage, current

Terminal instructions


EP1-E4AD



EP1-E4DA




EP1-E2AD2DA



Terminal definition

Marking	Explain
24V+	External 24V positive
24V-	External 24V negative
⊕	Earth
○	No connection
VOn+	Voltage signal output port of channel no.n
ION+	Current signal output port of channel no.n
VION-	Output common port of channel no,n
Vn+	Voltage signal input port of channel no.n
In+	Voltage signal input port of channel no.n
VIn-	Input common port of channel no.n

Dimensions



EM3 Series Human Machine Interface (HMI)



EM3 series human machine interface is a new HMI launched by Simphoenix. The new appearance of mental strip drawing is completely integrated into electrical control cabinet. It offers a better visual effect and excellent touch experience through Cortex A8 processor, 24-bite true-color display in collocation with configuration software Simphoenixface with rich functions.

Typical Applications

- Food Machinery
- Textile Machinery
- CNC Tools
- Rail Transit
- Wind Power Generation
- Electric Vehicles
- Building Automation



Features


- Industrial design standard with high requirements. Support reliable running in terrible condition
- High collocation and large storage: A8 processor platform 256MB FLASH+128MB DDR3
- New shape design: Brushed design of outer frame metal strip
- Support Ethercat communication (ethernet model only), convenient for multi-screen online
- The interface is downward and the cable is routed from the bottom to save the space of the control cabinet

Specifications

MODEL	EM3-070E	EM3-070T	EM3-101E	EM3-101T
Performance specifications				
Display module	7"TFT	7"TFT	10"TFT	10"TFT
Display color	65536			
Precision	800 × 480	800 × 480	1024 × 600	1024 × 600
Backlight type	LED			
Brightness	350cd/m²			
LCD life	30000 hours			
Touch type	4–wire precision resistor network			
CPU	600MHz 32 bits			
Memory	256M FLASH+128M DRAM			
Real Time Clock	Support			
USB HOST	USB2.0 × 1, Type A(USB1), Support U disk to update firmware,configuration and store data			
USB Slave	USB2.0 × 1, Type B(USB2), Support program upload and download			
Serial interface	COM1: RS485 COM2: RS232			
Ethernet	10M/100M adaptive	Not support	10M/100M adaptive	Not support
DB9	Plug, Non-isolated, RS485:7 – B, 8 - A, RS232:2 - RXD, 3 - RTX, 5 - GND			
Electrical Specifications				
Rated power	7.2W			
Rated voltage	DC24V			
Input range	20.4~28.8VDC			
Allow power loss	10ms			
Insulation resistance	Exceed 50MΩ @500VDC			
Withstand voltage performance	500 VAC 1min			
Structural specifications				
Shell color	Dark gray + Silver			
Shell material	ABS+PC plastic, metal			
Appearance dimension	230 × 166 × 39mm	230 × 166 × 39mm	272 × 212 × 39mm	272 × 212 × 39mm
Installation dimension	192 × 138mm	192 × 138mm	260 × 200mm	260 × 200mm
Weight	0.75Kg	0.75Kg	1.0Kg	1.0Kg
Environmental specifications				
Working temperature	0 ~ 50℃			
Working humidity	10 ~ 90%RH (No condensation)			
Storage temperature	-20 ~ 60℃			
Storage humidity	10 ~ 90%RH (No condensation)			
Anti–vibration ability	10 ~ 25Hz (2G/30min in X、Y、 Z)			
Cooling method	Air cooling			
Product certification				
Front panel protection level	IP65 (4208–93)			
CE certification	EN61000–6–2:2005/EN61000–6–4:2007			

EM3 Series

Interface Description



Installation and Dimension Figure

